



CTT 1000

STRETCH WRAPPER

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The CTT 1000 pallet wrapper can be easily integrated into an existing or new line. This film wrapper ensures that the total costs in your production line will decrease by using film with a high pre-stretch percentage and user friendly operation.

The CTT 1000 is a maintenance-friendly machine, can wrap up to 50 pallets per hour and the film is easy to replace with the fast-loading system.

Advantages

- Compact machine with limited installation dimensions
- Pre-stretch 7 steps: up to 400% using a patented system
- Processes up to 50 pallets per hour
- Wrapping speed 20 rpm
- Very accessible film trolley
- Ability to stack on the machine
- Standard equipped with roller conveyor in the machine

Options

- Higher packages, up to 3000 mm high
- For pallet weights up to 2000 kg
- Transport facility other than roller conveyor
- Movable mast for large load variation
- Larger diameter for different load sizes
- Adjusted transport height
- Pressure plate
- Roping system
- Seal unit
- Top sheet dispenser (inside)



> [Click here for a video of the CTT 1000](#) <



Technical data:	
Total power installed	2,5 kW
Standard power supply	400 V - 50 Hz - 3 PH+N+G
Protection on electric system	IP 54
Max. pallet dimensions	1000 x 1200 mm
Standard pallet height	2500 mm
Max. pallet weight	1500 kg
Standard diameter	Ø 1800 mm
Transport height	375 - 500 mm
Max. rotation speed	20 rpm
Capacity per hour	Up to 50 pallets / hour
Operating pressure	6 Bar

Cyklop UK Limited
 Unit 2, Generation Business Park
 Barford Road
 St. Neots
 Cambridgeshire
 PE19 6YQ

+44 1480 216777
www.cyklop.co.uk
info@cyklop.co.uk

